



## **Micro 26<sup>®</sup>-XD<sup>AC</sup>** **Electric Scissor Lift** **with Xtra-Deck<sup>®</sup>**

*Patent Pending*

- Pull-Down Xtra-Deck<sup>®</sup> Allows Access Through Ceiling Panels Providing a Safe Solution to Gaining Additional Height into Confined Spaces
- Compact Size Almost 2 ft. (60 cm) Shorter Than Other 26 ft. (7.6m) Lifts
- AC Electric Drive for Extended Duty Cycle, Smoother Control and Faster Drive Speed
- Spacious 2-Person Platform (Indoors)/ 1-Person Platform (Outdoors) with 550 lb. (250 kg) Capacity
- Fully Proportional Lift and Drive Controls
- 36 in. (90 cm) Roll-Out Deck Extension with Incremental Lock Positions

**Work Over 30 Ft. High Indoors in Tight Work Areas  
with Micro Footprint and Integral Xtra-Deck<sup>®</sup> Feature**



## Standard Features

### Work Area

Roll Out Deck Extension with Incremental Locking Positions  
 Standard Full Height Swing Gate  
 Lanyard Attachments (2)  
 Xtra-Deck® Additional 16 in. (.4 m) Height Platform *Patent Pending*

### Performance

AC Electric Drive  
 Fully Proportional Drive and Lift Controls  
 Up To 25% Gradeability

### Power

240Ah Maintenance-Free AGM Batteries  
 Battery Charge Indicator

### Serviceability

Lubrication-Free Scissor Bearings  
 Easy Maintenance Access to Mechanical and Electrical Components in  
 Swing Out Trays  
 Parking Brake Release Switch for Towing

### Safety

Lift Control Orientation Designed to Mitigate Entrapment  
 Dedicated Compartments Protect Electrical and Hydraulic Components  
 Emergency Shut-Off at Platform and Lower Controls  
 Non-Skid Metal Deck Construction  
 Xtra-Deck® Solution to Standing on  
 the Midrails Hazard  
 Descent Alarm  
 Drive Speed Interlock  
 Multi-Axis Tilt Sensor

Multiple Disk Brakes  
 Scissor Maintenance Lock  
 Automatic Parking Brakes  
 Automatic Pothole Protection

### Other Features

Removable Upper Controls  
 Voltage-Compensating Fully  
 Automatic Battery Charger  
 Hour Meter  
 Machine Tie Downs

Non-Marking Tires  
 All-Motion Alarm  
 Fork Lift Pockets  
 Flashing Beacon  
 Leak Containment System® (LCS)

## Optional Features

Upper Control Box Supplementary  
 Guard  
 900W Inverter  
 Tool Tray

Cold Weather Package  
 Pipe Rack  
 Proactive Platform Safety  
 System® (PPSS)  
 Second Year Extended Warranty



### MEC Aerial Work Platforms

Tel: 559.842.1500 | 1401 S. Madera Avenue, Kerman, CA 93630 | USA  
 Toll free: 1.877.MEC LIFT | 1.877.632.5438 | Fax: 559.842.1520  
 Email: info@MECawp.com | www.MECawp.com

MEC®, Micro 26®, Leak Containment System® & Proactive Platform Safety System® are registered trademarks of California Manufacturing & Engineering Co., LLC.  
 Leak Containment System® is Patent #11,112,060

97045 DTD 0424

Micro 26®-XD <sup>AC</sup>	U.S.	Metric
<b>Heights</b>		
Indoor Working Height*	31 ft.*	9.6 m*
Outdoor Working Height*	24 ft.*	7.5 m*
Indoor Platform Height	25 ft.	7.6 m
Outdoor Platform Height	18 ft.	5.5 m
Stowed Height (Top Guardrail)	90.3 in.	2.3 m
Stowed Height (Rails Folded)	78.75 in.	2 m
Stowed Height (Platform Floor)	47 in.	1.2 m
Guardrail Height	43.5 in	1.1 m
Toeboard Height	6 in.	0.15 m
Ground Clearance (Stowed)	3 in.	7.62 cm
<b>Dimensions</b>		
Length-Stowed (Overall)	74 in.	1.88 m
Length-Stowed (Ladder Removed)	68 in	1.73 m
Chassis Width	31.9 in	.81 m
Platform Length (Extended)	103.5 in.	2.63 m
Platform Length (Retracted)	68 in.	1.73 m
Roll-Out Deck Length	35.5 in.	.9 m
Platform Width (Outside)	29.1 in.	.74 m
Xtra-Deck® Width	22 in.	56 cm
Wheelbase	55 in.	1.4 m
Total Lift Capacity	550 lbs.	250 kg
Personnel Capacity	2 (Indoors); 1 (Outdoors)	
Roll-Out Deck Capacity	250 lbs.	113 kg
<b>Speed</b>		
Raise/Lower Speed	30/25 sec	
Drive Speed (Stowed)	3 mph	5 km/h
Drive Speed (Elevated)	.5 mph	.8 km/h
<b>Performance</b>		
Gradeability	25% 14 degrees	
Turning Radius (Inside)	6 in.	15 cm
Weight**	4,450 lbs.	2020 kg
Power Source	240Ah Maintenance-Free AGM Batteries	
Controls	Proportional	
Tires	12 in. x 5 in	30 cm x 12.5 cm

\*Metric equivalent of working height adds 2m to platform height. U.S. adds 6 ft. to platform height.  
 \*\*Weight may vary with certain options or configurations.

**Important** - MEC scissor lifts must be on a hard level surface while elevated.

**Warranty** - MEC Aerial Work Platforms carry a one (1) year warranty on defective component parts and a five (5) year warranty on defective structural parts. This warranty applies to the original owner only. Consult your MEC dealer for warranty details.

**Meets or exceeds** the requirements of ANSI A92.20 and CSA B354.6 - 2017.

**Specifications** subject to change without notice. Photos and diagrams in this brochure are for illustrative purposes only. Contact your MEC distributor for detailed instructions on the proper use and maintenance of this equipment.

Distributed by: