



# Micro 19

## Electric Scissor Lift

- Compact Size without Compromising Generous Work Area
- Fits on Most Elevators With Shortest Overall Length and Low GVW (Gross Vehicle Weight)
- 24 in. (60 cm) Roll-out Deck Extension with Incremental Lock Positions
- Direct Electric Drive for Extended Duty Cycle, Smoother Control and Fewer Leak Points
- 2-person Platform with 500 lb. (226 kg) Capacity
- Fully Proportional Lift and Drive Controls



**Ultra compact design fits into small and tight work areas**

## Standard Features

### Work Area

Roll-Out Deck Extension with Incremental Locking Positions  
 Standard Swing Gate  
 Lanyard Attachments  
 110v Power to Platform

### Performance

Direct Electric Drive  
 Fully Proportional Drive and Lift Controls  
 Up To 25% Gradeability

### Power

24v 115Ah AGM DC Electric Power (Maintenance-Free Batteries)  
 Battery Charge Indicator  
 Single 110v Receptacle at Chassis for Common Plug Connection for Battery  
 Charger and Power to Platform

### Serviceability

Lubrication-Free Scissor Bearings  
 Easy Maintenance Access to Mechanical and Electrical Components in a  
 Slide-Out Tray  
 Logically Grouped Components and Numbered Wiring for Easy Reference

### Safety

Lift Control Orientation Designed to Mitigate Overhead Entrapment	Non-Skid Metal Deck Construction
Dedicated Compartments Protect Electrical and Hydraulic Components	Descent Alarm
Emergency Shut-Off at Platform and Lower Controls	Drive Speed Interlock
	Scissor Maintenance Lock
	Multi-Axis Tilt Sensor
	Multiple Disc Brakes
	Automatic Parking Brake

### Other Features

Leak Containment System® (LCS)	Machine Tie Downs
Removable Upper Controls	Non-Marking Tires
Voltage-Compensating Fully Automatic Battery Charger	All Motion Alarm
Hour Meter	Fork Lift Pockets
	Flashing Beacon (Continuous)

## Optional Features

900W Inverter	Proactive Platform Safety System® (PPSS)
Tool Tray	Anti-Fatigue Mat
Pipe Rack	Second Year Extended Warranty
Cold Weather Package	



### MEC Aerial Work Platforms

Tel: 559.842.1500 | 1401 S. Madera Avenue, Kerman, CA 93630 | USA  
 Toll free: 1.877.MEC LIFT | 1.877.632.5438 | Fax: 559.842.1520  
 Email: info@MECawp.com | www.MECawp.com

MEC®, Micro 19®, Proactive Platform Safety System® and Leak Containment System® are registered trademarks of California Manufacturing & Engineering Co., LLC.  
 Leak Containment System® is Patent #11,112,060

94542 DTD 0224

Micro 19	U.S.	Metric
<b>Heights</b>		
Indoor Working Height*	24.4 ft.*	7.6 m*
Outdoor Working Height*	21 ft.*	6.6 m*
Indoor Platform Height	18.4 ft.	5.6 m
Outdoor Platform Height	15 ft.	4.6 m
Stowed Height (Top Guardrail)	79 in.	201 cm
Stowed Height (Platform Floor)	39 in.	99 cm
Guardrail Height	39 in.	99 cm
Toeboard Height	6 in.	15 cm
Ground Clearance (Stowed)	2.5 in.	6.4 cm
Ground Clearance (Elevated)	0.6 in.	1.5 cm
<b>Dimensions</b>		
Length-Stowed (Overall)	60 in.	152 cm
Length-Stowed (Ladder Removed)	54 in.	137 cm
Chassis Width	32 in.	81 cm
Platform Length (Extended)	78 in.	198 cm
Platform Length (Retracted)	54 in.	137 cm
Roll-Out Deck Length	24 in.	61 cm
Platform Width	27.5 in.	70 cm
Wheelbase	45 in.	114 cm
Total Lift Capacity	500 lbs.	227 kg
Personnel Capacity	2 ( Indoors); 1 (Outdoors)	
Roll-Out Deck Capacity	250 lbs.	113 kg
<b>Speed</b>		
Raise/Lower Speed	26 s	20 s
Drive Speed (Stowed)	2.5 mph	4.0 km/h
Drive Speed (Elevated)	0.5 mph	0.8 km/h
<b>Performance</b>		
Gradeability	25%	25%
Turning Radius (inside)	18 in.	46 cm
Weight**	2,750 lbs.**	1,250 kg**
Power Source	24 v DC, 115Ah AGM Battery Pack	
Controls	Proportional Drive & Lift Controls	
Tires	9 in. x 4 in.	23 cm x 10 cm

\*Metric equivalent of working height adds 2m to platform height. U.S. adds 6 ft. to platform height.  
 \*\*Weight may vary with certain options or configurations.

**Important** - MEC scissor lifts must be on a hard level surface while elevated.

**Warranty** - MEC Aerial Work Platforms carry a one (1) year warranty on defective component parts and a five (5) year warranty on defective structural parts. This warranty applies to the original owner only. Consult your MEC dealer for warranty details.

**Meets or exceeds** the requirements of ANSI A92.20 and CSA B354.6.

**Specifications** subject to change without notice. Photos and diagrams in this brochure are for illustrative purposes only. Contact your MEC distributor for detailed instructions on the proper use and maintenance of this equipment.

Distributed by: