



# TRIPLE L<sup>®</sup> TRAILERS



## Triple L® Trailers

# INCREASE PRODUCTIVITY WITH EFFICIENT, SAFER LOADING



4610 Flatbed Model

Load equipment and supplies faster and safer with the Triple L® trailer. Unlike ramp and tilt-bed systems, the Triple L trailer features the exclusive Power Deck system, a unique hydraulic mechanism used to lower the entire deck of the trailer to ground level. This eliminates the need to drive, pull, winch or push a payload up or down a loading ramp, which increases productivity and improves safety. The result is a more efficient solution for loading construction and industrial equipment, machines and supplies.

Even hard-to-load equipment becomes a one-person job with a Triple L flatbed trailer. These models are ideal for carrying equipment with low ground clearance or poor traction such as scissor lifts, industrial sweepers, landscaping equipment, pavers, rollers, compactors and more. With nine models to choose from and capacities up to 10,000 pounds—you'll always find the right solution with a Triple L trailer.



UT914 Utility Model

## CONVENIENT LOADING FOR EASE OF TRANSPORT

Triple L utility trailers load as quickly and easily as flatbed models, with the added convenience of enclosed sides. These dual-purpose models are ideal for carrying equipment or supplies. A full width, low angle ramp allows for easier loading with a handcart or dolly. Choose from eight models with capacities up to 10,000 pounds. Optional rails and a tailgate can be added or removed at any time for added convenience.

### IMPROVED SAFETY:

- Keeps all loading and unloading at ground level.
- Eliminates chances of dropping cargo off ramps.
- No climbing to access machine tie-downs.
- No heavy, hinged ramps that can come loose or drop.

# POWER DECK ADVANTAGE




- Single lever hydraulic control
- Keeps all loading and unloading at ground level.
- Eliminates chances of dropping cargo off ramps.
- No climbing to access machine tie-downs.
- No heavy, hinged ramps that can come loose or drop.



**LOWER**  
entire deck to  
ground level.



**LOAD**  
equipment




**LIFT**  
to transport  
position



## Large Deck

Up to 72 inches wide to hold more payload.



## Quadra Spring Suspension

For smoother transport.



## Low Angle Ramp

For low clearance loading.



## Shielded Tail Lights

Added protection with improved visibility.



## Storage Compartments

Protects components and tools; lockable.



## Fenderless

No protruding fenders that are susceptible to damage.



## Unhitched Loading

Trailer can be loaded while hitched or freestanding.



## Single Lever Control

12-volt hydraulic system is proportional in both directions.



## Automatic Deck Latch

Deck automatically locks upon raising for added security.




## Powder Coating

Provides durable protective finish.



# Triple L® Trailers

## OPTIONS & ACCESSORIES



**Winch**  
12-volt loading winch with 12-foot remote control. Flatbed model



**Spare Tire & Bracket**  
Mounts conveniently within the width of the chassis.



**Surge Brakes**  
Heavy-duty actuator with adjustable coupler.



**Extended Side Rails**  
Bolted to existing rails for 36 in. or 48 in. heights. UT model only



**Tailgate**  
Full width swinging tailgate can easily be removed. UT model



**Pintle Hitch**  
Interchanges and replaces standard ball coupler.

FLATBED MODEL	449	4610	7610	7612	7614	7616	1012	1014
<b>Capacity</b>	5,000 lb (2,268 kg)	4,500 lb (2,041 kg)	7,000 lb (3,175 kg)	7,000 lb (3,175 kg)	7,000 lb (3,175 kg)	6,500 lb (2,948 kg)	10,000 lb (4,536 kg)	10,000 lb (4,536 kg)
<b>Deck Width</b>	4' 4 in. (1.32 m)	6 ft (1.83 m)	6 ft (1.83 m)	6 ft (1.83 m)	6 ft (1.83 m)	6 ft (1.83 m)	5 ft 10 in. (1.78 m)	5 ft 10 in. (1.78 m)
<b>Deck Length</b>	9 ft (2.74 m)	10 ft (3.05 m)	10 ft (3.05 m)	12 ft (3.66 m)	14 ft (4.27 m)	16 ft (4.88 m)	12 ft (3.66 m)	14 ft (4.27 m)
<b>Overall Length</b>	14 ft (4.27 m)	15 ft (4.57 m)	15 ft (4.57 m)	17 ft (5.18 m)	19 ft (5.79 m)	21 ft (6.4 m)	17 ft (5.18 m)	19 ft (5.79 m)
<b>Trailer Weight*</b>	1,670 lb (758 kg)	2,070 lb (939 kg)	2,500 lb (1,134 kg)	2,690 lb (1,200 kg)	2,930 lb (1,329 kg)	3,150 lb (1,429 kg)	3,010 lb (1,365 kg)	3,210 lb (1,456 kg)
<b>Lift Mechanism</b>	Hydraulic	Hydraulic	Hydraulic	Hydraulic	Hydraulic	Hydraulic	Hydraulic	Hydraulic
<b>Axle</b>	Single	Single	Tandem	Tandem	Tandem	Tandem	Tandem	Tandem
<b>Wheel Size</b>	16 in. (0.41 m)	14.5 in. (0.37 m)	15 in. (0.38 m)	15 in. (0.38 m)	15 in. (0.38 m)	15 in. (0.38 m)	16 in. (0.41 m)	16 in. (0.41 m)
<b>Brakes</b>	Electric	Electric	Electric	Electric	Electric	Electric	Electric	Electric
<b>Hitch — Ball Size</b>	2-5/16 in (0.58 m)	2-5/16 in (0.58 m)	2-5/16 in (0.58 m)	2-5/16 in (0.58 m)	2-5/16 in (0.58 m)	2-5/16 in (0.58 m)	2-5/16 in (0.58 m)	2-5/16 in (0.58 m)

UTILITY MODEL	UT49	UT410	UT610	UT612	UT614	UT912	UT914
<b>Capacity</b>	5,000 lb* (2,268 kg)	4,500 lb (2,041 kg)	7,000 lb (3,175 kg)	7,000 lb (3,175 kg)	6,500 lb (2,948 kg)	10,000 lb (4,536 kg)	10,000 lb (4,536 kg)
<b>Deck Width</b>	4 ft 4 in. (1.32 m)	6 ft (1.83 m)	6 ft (1.83 m)	6 ft (1.83 m)	6 ft (1.83 m)	5 ft 10 in. (1.78 m)	5 ft 10 in. (1.78 m)
<b>Deck Length</b>	9 ft (2.74 m)	10 ft (3.05 m)	10 ft (3.05 m)	12 ft (3.66 m)	14 ft (4.27 m)	12 ft (3.66 m)	14 ft (4.27 m)
<b>Overall Length</b>	14 ft (4.27 m)	15 ft (4.57 m)	15 ft (4.57 m)	17 ft (5.18 m)	19 ft (5.79 m)	17 ft (5.18 m)	19 ft (5.79 m)
<b>Trailer Weight*</b>	1,795 lb (814 kg)	2,220 lb (1,007 kg)	2,650 lb (1,202 kg)	2,850 lb (1,293 kg)	3,050 lb (1,383 kg)	3,170 lb (1,438 kg)	3,370 lb (1,529 kg)
<b>Lift Mechanism</b>	Hydraulic	Hydraulic	Hydraulic	Hydraulic	Hydraulic	Hydraulic	Hydraulic
<b>Axle</b>	Single	Single	Tandem	Tandem	Tandem	Tandem	Tandem
<b>Wheel Size</b>	16 in. (0.41 m)	14.5 in. (0.37 m)	15 in. (0.38 m)	15 in. (0.38 m)	15 in. (0.38 m)	16 in. (0.41 m)	16 in. (0.41 m)
<b>Brakes</b>	Electric	Electric	Electric	Electric	Electric	Electric	Electric
<b>Hitch — Ball Size</b>	2-5/16 in (0.58 m)	2-5/16 in (0.58 m)	2-5/16 in (0.58 m)	2-5/16 in (0.58 m)	2-5/16 in (0.58 m)	2-5/16 in (0.58 m)	2-5/16 in (0.58 m)

\*Will vary slightly with optional equipment.  
Battery included

Triple L Group, LLC

Address: 14323 Fern Ave., Chino, CA 91710

Website: [www.TripleL.com](http://www.TripleL.com)

Email Inquiries: [sales@triplel.com](mailto:sales@triplel.com)

Phone #: +1-844-8TRIPLE | +1-844-887-4753