

FEATURES

- Award Winning i-Power System
- Ramp Control
- Elevated Creep Mode
- Variable Steer Speed
- Direct Electric Drive
- Re-Gen Power
- Lightweight
Perfect for mezzanine applications
1230i = 1,688 lbs (766 kg)
1530i = 1,975 lbs (895 kg)
- Power Take Off
- Elevated High Torque Mode
- AGM Batteries
- Battery Management System
- Compact Design
Fits through a standard door without having to fold the guardrails. Folding guardrails are a standard feature which provide a compact footprint for easy storage.



SPECIFICATIONS

	1230i		1530i	
Measurements	US	Metric	US	Metric
Working height maximum	17.8'	5.5 m	20.9'	6.5 m
Platform height maximum	11.8'	3.6 m	14.9'	4.5 m
Platform height - stowed	33"	.83 m	37"	.95 m
Platform length - retracted	4.3'	1.29 m	4.3'	1.29 m
Platform length - extended	6.3'	1.89 m	6.3'	1.89 m
Slide-out platform extension deck	24"	60 cm	24"	60 cm
Platform width - outside	28"	70 cm	28"	70 cm
Toeboard height	6.7"	17 cm	6.7"	17 cm
Height - stowed	75"	1.94 m	79"	2.01 m
Height - rails folded	63"	1.6 m	67"	1.7 m
Length stowed	57"	1.44 m	57"	1.44 m
Length w/o ladder	50.5"	1.28 m	50.5"	1.28 m
Width	30"	.76 m	30"	.76 m
Wheelbase	41"	1.05 m	41"	1.05 m
Ground clearance - center	2.5'	6.4 cm	2.5'	6.4 cm
- pothole bars deployed	.7"	2.0 cm	.7"	2.0 cm
Productivity	US	Metric	US	Metric
Maximum platform occupancy	2			
Lifting capacity	530 lbs / 240 kg			
Extension deck capacity	220 lbs / 100 kg			
Drive height	Full Height			
Drive speed - stowed	2.5 mph / 4 km/h			
Drive speed - raised	0.5 mph / 0.8 km/h			
Drive speed - raised creep mode	0.1 mph / 0.16 km/h			
Gradeability - stowed	30%			
Turning radius - inside	15" / 38 cm			
Raise speed	19 seconds		22 seconds	
Lower speed	19seconds		22 seconds	
Controls	Fully Proportional			
Drive	Direct Electric			
Tires - Solid, Non-marking	9" x 3" / 22.8 x 7.6 cm			
Power	US	Metric	US	Metric
Power Source	24v, 95Ah			
Weight	US	Metric	US	Metric
ANSI / CE	1,688 lbs	766 kg	1,975 lbs	895 kg

STANDARD EQUIPMENT

- Industrial grade, solid state battery charger
- Non-marking tires
- Machine tie-downs
- Hour meter
- Forklift pockets
- Platform swing gate
- Lanyard attachments

PERFORMANCE

- Fully proportional lift controls

SAFETY

- Emergency shut-off at platform and lower controls
- Non-skid platform deck
- Decent alarm
- Multi-axis tilt sensor
- Scissor maintenance lock
- Multiple disc brakes
- Emergency lowering system

SERVICEABILITY

- Easy maintenance access to mechanical and electrical components



www.goGMG.com